

BT22 LP Biosynthetic® Base Oil

Delivering innovations for a sustainable future.



BT22 LP - **LOW POUR** - is a medium viscosity, lubricant base oil designed specifically to help customers in the lubrication industries meet their production quality standards in application, where a low pour point is essential. This renewable base oil is 99% bio-based and offers a pour point of **-42°C**.

TECHNICAL PERFORMANCE

- Low Volatility
- High Viscosity Index
- Great Hydrolytic Stability
- Natural Detergency
- Longer Lasting
- Increased Safety
- Fewer Additives Needed
- Less Maintenance
- **Low Pour Point**

ENVIRONMENTAL BENEFITS

- High Biodegradability
- Low Bioaccumulation
- Low Toxicity
- High Bio-Content
- Rapid Breakdown
- Low Environmental Risk
- Reduced Risk to Wildlife
- Renewable Carbon Based



MED VISCOSITY

150

ISO VG

BIODEGRADABLE

84 %

(OECD 301B)

BIO-BASED

99 %

(ASTM D6866)

APPLICATIONS



Cold Temperature Applications



Motor Oil



Hydraulic Fluid



Compressor Oil

SEE REVERSE FOR PRODUCT SPECIFICATIONS

For more info contact us at info@biosynthetic.com or visit our website: www.biosynthetic.com
Biosynthetic Technologies, LLC. | 6320 Intech Way, Indianapolis, IN 46278 | 317-556-1050
www.linkedin.com/company/biosynthetic-technologies
REV 1.2 - 1/2020

BT22 LP Product Specifications



PHYSICAL PROPERTIES

Property	Unit	Method	Typical Result*
Viscometrics			
Kinematic Viscosity at 100°C	cSt	D445	22.4
Kinematic Viscosity at 40°C	cSt	D445	143.9
Viscosity Index	-	D2270	185
Cold Temperature			
Pour Point	°C	D97	-42
Volatility			
Flash Point	°C	D92	270
Titration			
Total Acid Number	mg KOH/g	D664	0.2
Others			
Color	-	D1544	5
Water	wt%	D1533	0.1 max
Specific Gravity (15°C)	-	D4052	0.92-0.94

*Typical results are provided. To the best of our knowledge, the information is accurate, but given without guarantee. All results are for an unadditized base oil.



ENVIRONMENTAL PROPERTIES

Biodegradability	OECD 301B	84%
Renewable Carbon Content	ASTM D6866	99%
EcoToxicity	OECD 201	>1000 mg/L
	OECD 202	>1000 mg/L
	OECD 203	>1000 mg/L

PERFORMANCE TESTING

4-Ball Wear	ASTM D4172	TBD
4-Ball Weld	ASTM D2783	
Weld Load		TBD
Load-Wear Index		TBD
Hydrolytic Stability	ASTM D2619	
Total Acidity Water Layer		TBD

Typical properties depicted on this document are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.